




COSMIC FLUID

LIQUID ADHESIVE
FOR ACOUSTIC FOAM MATERIALS



DIRECTIONS FOR USE

All surfaces must be dry and free from dust, grease and any loose material. Paint should be removed where the adhesive will make contact. New concrete or plaster should be allowed adequate time to dry and mature. Loose, crumbly or porous surfaces should first be smoothed and/or primed with a dilute solution of contact adhesive and allowed to dry.

Apply Cosmic Fluid Adhesive as a continuous bead approximately 6mm diameter around the edges of the panel and in horizontal lines at approximately 450mm centres. Immediately press the panel firmly to the wall surface to ensure adequate transfer of adhesive and leave to set. A firm bond is achieved in about 1 hour.

Tack Life: 5-30 mins

Coverage: 11 metres per cartridge
6mm bead

Shelf Life: 12 months stored
@ 4 ~ 25°C

The adhesive is non-staining.

PRECAUTIONS

Skin contact: Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor. **Ingestion:** Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor. **Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

Irritating to skin. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of harm to the unborn child. Keep out of the reach of children. Wear suitable protective clothing and gloves. Avoid release to the environment. Refer to special instructions / safety data sheets. Restricted to professional users.

By purchasing this product the user accepts responsibility for determining suitability of use. Universal Acoustics Ltd accept no liability for any loss or damage incurred whether direct or indirect in connection with the use of this product.

310ml



UNIVERSAL
ACOUSTICS LTD

PO BOX 4601, KILN FARM,
MILTON KEYNES
MK19 7ZN

www.universal-acoustics.com



5 0 6 0 2 4 0 1 5 0 0 0 7

TRANSPORT INFORMATION:

UN No: 1133

UN shipping name:
ADHESIVES

Transport Hazard class:
ADR/RID class 3



SIGNAL WORD DANGER

Hazard statements: **H412** Harmful to aquatic life with long lasting effects. **H225** Highly flammable liquid and vapour.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. **P260** Do not breathe vapours. **P280** Wear protective gloves/protective clothing/eye protection/face protection. **P281** Use personal protective equipment as required. **P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **P313** Get medical advice/attention. **P501** Dispose of contents/container in accordance with national regulations.

Contains:

Hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane