

SAFETY DATA SHEET A00071

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name COSMIC FLUID

Product number A00071

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier UNIVERSAL ACOUSTICS LTD

P.O. BOX 4601 KILN FARM MILTON KEYNES

BUCKS MK19 7ZN

T: +44 (0) 845 555 1123

E: info@universal-acoustics.com W: www.universal-acoustics.com

1.4. Emergency telephone number

Emergency telephone +44 01827 69662 (NOT 24HRS)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225

Health hazards Not Classified

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or F;R11. R52/53.

1999/45/EC)

Physicochemical The product is highly flammable. Vapours may form explosive mixtures with air. Vapours are

heavier than air and may travel along the floor and accumulate in the bottom of containers.

Vapours may be ignited by a spark, a hot surface or an ember.

2.2. Label elements

Pictogram



A00071

Signal word Danger

Hazard statements H412 Harmful to aquatic life with long lasting effects.

H225 Highly flammable liquid and vapour.

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P260 Do not breathe vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P313 Get medical advice/attention.

P501 Dispose of contents/container in accordance with national regulations.

Contains hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-

10-30%

hexane

CAS number: — EC number: 921-024-6 REACH registration number: 01-

2119475514-35

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

Skin Irrit. 2 - H315 Asp. Tox. 1 - H304 STOT SE 3 - H336 STOT SE 3 - H336 STOT SE 3 - H336 Aquatic Chronic 2 - H411

XYLENE 1-5%

CAS number: 1330-20-7 EC number: 215-535-7 REACH registration number: 01-

2119488216-32

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 3 - H226 R10 Xn;R20/21 Xi;R38

Skin Irrit. 2 - H315 Acute Tox. 4 - H312 Acute Tox. 4 - H332

A00071

HEXANE-norm <1%

CAS number: 110-54-3 EC number: 203-777-6 REACH registration number: 01-

2119480412-44

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Repr. Cat. 3;R62 Xn;R48/20,R65 Xi;R38 R67

Skin Irrit. 2 - H315 N;R51/53

Repr. 2 - H361f Asp. Tox. 1 - H304 STOT SE 3 - H336 STOT RE 2 - H373 STOT SE 3 - H336 STOT SE 3 - H336 Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing.

Ingestion Rinse mouth thoroughly with water. Get medical attention.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant

foam, carbon dioxide or dry powder.

Unsuitable extinguishing

nedia

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Protection against

nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. The product

is highly flammable.

A00071

Hazardous combustion

products

Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during

firefighting

Control run-off water by containing and keeping it out of sewers and watercourses. Avoid

breathing fire gases or vapours. Keep up-wind to avoid fumes.

Special protective equipment

for firefighters

Wear chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the

Environmental Agency or other appropriate regulatory body. Do not discharge into drains or

watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near

spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into

containers.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste

disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautionsKeep away from heat, sparks and open flame. Static electricity and formation of sparks must

be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the

original container.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m3(Sk) Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m3(Sk)

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

Short-term exposure limit (15-minute): WEL

A00071

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment









Appropriate engineering

controls

exposure limits for the product or ingredients. The following protection should be worn: Chemical splash goggles.

Hand protection

Eye/face protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves.

Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational

Hygiene measures Use engineering controls to reduce air contamination to permissible exposure level. Provide

eyewash station. Wash contaminated clothing before reuse. Wash hands after handling.

Eating, smoking and water fountains prohibited in immediate work area.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator

fitted with the following cartridge: Combination filter, type A2/P3.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to

reduce emissions to acceptable levels.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Colour Amber.

Odour Characteristic. Odour threshold Not available.

pН Estimated value. pH (concentrated solution): 7-8

Not available.

Melting point Not available.

Initial boiling point and range Not determined.

-35°C Flash point

Not determined. **Evaporation rate Evaporation factor** Not available. Flammability (solid, gas)

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 0.6 Upper flammable/explosive limit: 13

A00071

Other flammability

Vapour pressure

Not available.

Vapour density

Not available.

Relative density

0.86 @ 20°C

Bulk density

Not available.

Solubility(ies) Insoluble in water.

Partition coefficient Not available.

Auto-ignition temperature 200°C

Decomposition Temperature Not available.

Viscosity > 20.5 mm²/s.

Explosive properties Not available.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties Not available.

Comments Information given is applicable to the product as supplied.

9.2. Other information

Other information No information required.

Refractive index

Particle size

Not available.

Molecular weight

Not available.

Volatility

Not available.

Saturation concentration

Not available.

Critical temperature Not available.

Volatile organic compound This product contains a maximum VOC content of 400 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns. Stable at normal ambient temperatures and when used as

recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not applicable. Not relevant.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

A00071

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 22,916.67

Acute toxicity - inhalation

ATE inhalation (gases ppm) 93,750.0
ATE inhalation (vapours mg/l) 229.17
ATE inhalation (dusts/mists 31.25

mg/l)

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient Not available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1133 UN No. (IMDG) 1133 UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper shipping name

ADHESIVES

(ADR/RID)

A00071

Proper shipping name ADHESIVES

(IMDG)

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID subsidiary risk

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk

ICAO class/division 3

ICAO subsidiary risk

Transport labels



14.4. Packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •3YE

Hazard Identification Number 33

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Compliance

Revision date 15/07/2015

A00071

Revision 20

Risk phrases in full R10 Flammable.

R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R62 Possible risk of impaired fertility.

R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Store Between 5'c - 25'c